



MX-8

©2008



- 
- -
 -
- 

Arial

[] []

{ x|y|... }

[x|y|...]

//

1.



2.



3.



Enter a

a

1+ 2
Alt A

Ctrl+Alt+A Ctrl

1 2

Alt F Alt

F



1

1.1

- RingMaster —
- MX MP — WLAN
- Mobility Point (MP) (RF) — MX
- Mobility System Software (MSS) — MP Web WLAN RingMaster MX

1.2 MX-8

MX-8 MX

 MP


 8 10/100Mbps 6

PoE 12 MP



2-1 MX-8





LED

LED		
Power		MXI

	<ul style="list-style-type: none"> • RFC 1591 DNS • RFC 2030 SNMP • RFC 768 UDP • RFC 783 TFTP • RFC 791 IP • RFC 792 ICMP • RFC 793 TCP • RFC 826 ARP • IEEE 802.1D Spanning Tree • IEEE 802.1Q VLAN tagging • IEEE 802.3ad (static config)
	<ul style="list-style-type: none"> • RFC 854 Telnet (server and client) • SSHv2 - Secure Shell V2 • SNMP v1/ v2c/ v3 • RFC 1213 MIB-II • RFC 1866 HTML • RFC 2068 HTTP • RFC 3164 Syslog • private MIB • IETF CAPWAP
IP	<ul style="list-style-type: none"> • RFC 1112 IGMP v1 • RFC 2236 IGMP v2
QoS	<ul style="list-style-type: none"> • 802.1p QoS on Ethernet • 802.11e, Wi-Fi Multimedia (WMM) • SpectraLink Voice Priority (SVP) • RFC 2472 DiffServ precedence • RFC 2597 DiffServ Assured Forwarding • RFC 2598 DiffServ Expedited Forwarding

2



u
u

2.1



LED

MX-8

u

2.2

console

9600/8bit/1 stop/no pority/hardware flow control off



§

<