

RG - AP520(HD)

V1.0

III

Ч Ч Ч

Ч Ч Ч III



III

III

Ч III Ч III

III III

III III

III

¶

¶

III

III

III

<http://www.ruijie.com.cn/>

<http://webchat.ruijie.com.cn>

<http://www.ruijie.com.cn/service.aspx>

7 § 24

4008-111-000

<http://bbs.ruijie.com.cn/portal.php>

<http://www.ruijie.com.cn/service/know.aspx>

4008111000@ruijie.com.cn

1

RG-AP520(HD)		802.11ac wave2		AP III	
RG-AP520(HD)		802.11a/n/ac 802.11b/g/n		300Mbps	
802.11n	866Mbps	802.11ac	III	RG-AP520(HD)	1 1000Mbps RJ-45
III					

1.1

1.1.1 RG-AP520(HD)

RG-AP520(HD)

(L § W § H)	160mm *135 mm *40mm
	1 WAN/POE
	3dBi
	Ů100mw 20dBm
	1dBm
	802.3af/802.3at
	<8W
	-30~60 Ň
	5~95%RH
	0.6kg
Flash	256Mb
	IP67

2 RG-AP520(HD)

2.1

RG-AP520(HD) III

” III
” III
” III
” Ч III
” Ч III

a

A

2.2

III

2.2.1

Ч
” III
” III
” Ч III

2.3

1) 2) 3) III

3 RG-AP520 HD

3.1 RG-AP520 HD

3.2

2cm 6 2.5cm

/ / ø 9X25.4mm

3.3

4

4.1

RG-AP520(HD)

)

Telnet

IP

192.168.120.1

III

radio1

WIFI-XXXXXX(XXXXXX

ap mac

IP

192.168.120.2

255.255.255.0

SSID

"

a

-

RG-AP520 HD

1	RG-AP520 HD	1		
2	RJ45	1		
4		1		
5	, ST4.2X20	4		
6	, ö 9X25.4mm	4		
7	,AP740 ,125*14.5*6(mm)	1/12		1