



1		
2		5
3		6
4		8
5		11



1080P	RG-IIB-K75AS/K86AS	A LED	
	4K		
	RG-IIB-K75AS/K86AS		
	178		
	RG-IIB-K75AS/K86AS		
	RG-IIB-K75AS/K86AS	7H	AG
	RG-IIB-K75AS/K86AS		
	Touch		
	HDMI		
	RG-IIB-K75AS/K86AS	OPS	Windows
Andorid	Android8.0	64	
		Android	
		Intel	OPS-C CPU
	OPS		
	RG-IIB-K75AS/K86AS	OPS	
		Windows	

	RG-IIB-K75AS	RG-IIB-K86AS
	75	86
	16:9	16:9
	3840X2160	3840X2160
	450cd/	400 cd/
	60Hz	60Hz
	178°/178°	178°/178°
MTBF	≥200000	≥200000
	20	

VGA in×1

VGA in×1

PC-Aud

	100 V ~ 240 V/AC, 50/60 Hz	100 V ~ 240 V/AC, 50/60 Hz
OPS-C	400W	440W
	<=0.5W	<=0.5W
(W*D*H)	1741.7mmx103.4mmx1060.2mm	1995.2mmx111.9mmx1206.3mm
(W*H*D)	1880mmx280mmx1160mm	2140mmx280mmx1340mm
	59.1±1.5KG	76.6±1.5KG
	77.6KG±1.5KG	97.0KG 1.5KG



RG-IIB-K75AS	20	75	4K	20
		OPS		
RG-IIB-K86AS	20	86	4K	20
		OPS		
RG-BoardMate-H				
				®
RG-BoardMate-B				
RG-OPS-C-I3V1	Intel	OPS-C		® ™ i3

