

RG-S5750-S





Contents



Contents

Ctrl Version: RGOS 10.4(3b16) Release(146430)
MTD_DRIVER-5-MTD_NAND_FOUND: 1 NAND chips(chip size : 134217728) detected
1 nand chip(s) found on the target.
Press Ctrl+C to enter Ctrl ...

// log 3s ctrl+c CTRL

Hot Commands:

Ctrl > ^C

Ctrl > ^C

Ctrl > rename config.text config.bak

Ctrl > load //

Ruijie#copy flash:config.bak flash:config.text

Ruijie#copy startup-config running-config

Ruijie# configure terminal

Ruijie(config)#enable secret level 15 0 ruijie // enable

Ruijie(config)#line vty 0 4

Ruijie(config-line)#password 0 ruijie // telnet

Ruijie(config-line)#login

Ruijie(config-line)#end

Ruijie#write //



Contents



www.ruijie.com.cn

RGOS

Ruijie#copy



SystC 2(m 14()9(seriSpe

zy(BT/F8 9.96 Tf1 0



Contents

Ruijie#show tempr

Device-1:

Current Tempr: 29.0 C

	指示灯灭	端口未 Link		
000M Link Up			绿色常亮	端口 1
000M 数据收发	1000Mbps RJ-45 接口指示 灯	1-24	绿色闪烁	端口 1
00/10M Link Up			黄灯常亮	端口 1
00/10M 数据收发			黄灯闪烁	端口 1

```
Ruijie#show fans
```

```
Device-1:
```

Item	Status	Serial Number	Ver	Speed
1	Normal	-	1	//normal
2	Normal	-	1	



CPU • i V i - Ü ä ½ Â K 3 °) T ¿ ! € \$ ñ † A ' 0 L



Ruijie#show interfaces counters

```
Interface : GigabitEthernet 0/1
5 minutes input rate : 1034 bits/sec, 1 packets/sec
5 minutes output rate : 65 bits/sec, 0 packets/sec
InOctets          : 8918550
InUcastPkts      : 4
InMulticastPkts  : 103298
InBroadcastPkts  : 0
OutOctets         : 524352
OutUcastPkts     : 4
OutMulticastPkts : 2298
OutBroadcastPkts : 0
Undersize packets : 0
Oversize packets : 0
collisions       : 0
Fragments        : 0
Jabbers          : 0
CRC alignment errors : 0
AlignmentErrors  : 0
FCSErrors        : 0
dropped packet events (due to lack of resources): 0
packets received of length (in octets):
```





Contents















-

-

-

-

-