￼	￼	￼	￼
2012-06	V1.0		
2015-03	V1.1		

Contents

ㅏ ㅅ Ą

ㅓ

ㅗ ㅎ

ㅜ

ㅡ ㅣ

α̋ 6

RSR20

RSR20-14E/F

MSTP

But

Contents

Φ Ŭ

ϟ ≒

ɨ

بﺍ

ǟ 6

° ´	RSR20-14E
ڶ ب ل	1 Console 1 AUX 1 USB 1 SD 1 ۃ أ ۼ 24 10/ 100 ل 2 ɔ 2 SFP 2 ɔ ۃ
SIC Rs	4 ۃ ⋮ ـ ا ب ل 4 SIC
BOOT ROM	8MB
NAND FLASH	128MB
DDR II	512MB
(W×H×D)	440mm×43.6mm×300mm (1U)
ڑ ɔ	AC100 240V 50~60Hz
ǎ	50W
ע □	0 45
ע □	-40 70
►	10 95%RH

1	SLOT 2	2	SLOT 3
3	SLOT 4	4	SLOT 5
5	ɔ ◊	6	ɔ ◊
7		8	

1	SLOT2	2	SLOT3
3	SLOT4	4	SLOT5
5	SLOT6	6	
7	◊ כ	8	◊ כ ڑ

RSR20-14E/FW

- SIC
  - SIC-1HS
  - SIC-1E1-F
  - SIC-ISDN-S/T
  - SIC-1B-U
  - SIC-8A
  - SIC-2FXS
  - SIC-2FXO
  - SIC-1CE1
  - SIC-3G-TD
  - SIC-3G-WCDMA
  - SIC-3G-CDMA
  - SIC-SEC
- NMX
  - RSR20-14F(V1.X) NMX-24ESW





ð RSR20 SIC p Rs ت ٣ Rs ز ‰
├ ⅛ Rs ĩ 1 SIC Rs 1 SIC

SIC ٦ 1 ٧ f

类型	RSR20-14E 支持的 SIC 线卡
A 类	SIC-4BSV、SIC-4BLV、SIC-1B-S/T、SIC-2EXS、SIC-2EXC、SIC-2FC、
DMA、SIC-3G-WCDMA、	B 类 SIC-1HS、SIC-3G-1D、SIC-3G-C
	C 类 SIC-1CE1、SIC-1E1-F
	D 类 暂无支持的 D 类卡

RSR20-14E₩

RSR20-14E ¡¡ SIC †
ABCD
SIC 4

SIC	2	3	4	5	
SIC-4ESW	X	X	X	X	
SIC-1CE1					4
SIC-1E1-F					4
SIC-1HS					4
SIC-3G-TD					3
SIC-3G-WCDMA					3
SIC-3G-CDMA					3
SIC-SEC					1
SIC-1A	X	X	X	X	
SIC-8A					4
SIC-1B-U					*4*
SIC-1B-S/T					*4*
SIC-2FXS					4
SIC-2FXO					4

₦ ₌ ڜ	RSR20-04	RSR20-14	RSR20-24	RSR20-14E	RSR20-14F
Consol/AUX	2 ` ♀.	2 ` ♀.	2 ` ♀.	2 ` ♀.	2 ` ♀.
≠	2FE	3FE	2FE	2GE ≠ ∀	2GE ≠ ∀
	0	0	0	2	1
≠	0	0	0	24FE	48FE
˜ ~	4	24	52	24	48(v2.x` ) 72(v1.x`)
SD/CF	0	0	0	1	1
USB	0	2	2	1	1
SIC †	4				

Contents

Φ Ǔ

ﻯ

6

4 ◕

- ₩ ﻝ ث ٠ أ ث ٠ ٹ ـِ ﻝ ب ق إ ـ
  س ₩ ﻝ ب
- ﻝ ب OBJ ﻝ ب OBJ ٧
- ₩ ب ﻝ ﻝ ٨ ٦ SVI

4 ٬

- RSR20-14E : fastEthernet 1/0 - fastEthernet 1/23
- RSR20-14F : fastEthernet 1/0 - fastEthernet 1/47

NMX-24ESW ١ ₱

- ﻝ ب ` أ أ ﻝ ب ـِ ٹ ٠ ٹ أ
  ð ٹ ٠ ٹ
- NMX-24ESW أً RSR20-14F ð ب ﻝ ¯ ٦ SVI
  ﻝ ب
- RSR20-14F ð̈ RSR20 ٦ OBJ ¯ OBJ ` OBJ ð̈
  RSR20 ¯ service-module fastEthernet 2/0 session
- RSR20-14F ؟ ١ ’ ˚ ´ گ أ إ ـ
  ث ٠ RSR20 ک ٹ ئ ڈ ۋ ١ . ■ OBJ أ
  أ ـ V1.2.doc

₩ بـلـ

vlan

```
Ruijie(config)#vlan 2
Ruijie(config-vlan)# name ا لـ
Ruijie(config-vlan)#!
Ruijie(config-vlan)#vlan 3
Ruijie(config-vlan)# name ð إ ˇ
Ruijie(config-vlan)#!
Ruijie(config-vlan)#vlan 4
Ruijie(config-vlan)# name إ ـ
```

ˆ vlan

```
Ruijie(config)#interface fastEthernet 1/0
Ruijie(config-if)#switchport access vlan 2
Ruijie(config)#interface fastEthernet 1/1
Ruijie(config-if)#switchport access vlan 3
Ruijie(config)#interface range fastEthernet 1/2
- 4
Ruijie(config-if-range)#switchport access vlan
4
//      range[OBJ]بـلـ
```

SVI

```
Ruijie(config)#interface VLAN 2
Ruijie(config-if
```

⁴ ڀ ڑ ڊ ڈ ٥ ف ٨ trunk ٧ ٨ ٧ ٨

- ð RSR20 VLANٹ ċ

ٮ RSR20ف ٨ ڤ ٻ

ð RSR20ٹ ٠ Ă ٫ V1.2.doc

⁴ ᵘ ⅄

- VLAN/TRUNK
- ᵎ AP
- ⅄ IP ⅃
- ⅄ ᔑ ᔕ
- 802.1X ɲ -
- ı ‴

⁴ ᵑ ᵘ ⅄

- ᔑ ⅃ ᵔ ᵔ
- ⅄ ᔑ
- RLDP
- IGMP SNOOPING
- ACL

ʊ ĺ ∩ ѵ

Show cpu ´H

show cpu ج₩ ŕ CPU° ◊ڤΦ ﾉ ɯ ' ﻩ ا ج° ◊ ﾉ ɯ

ن ص ٨

Ruijie(support)#ef_statics_switch ?
<0-1> 0-1

0 ڑ ج° ◊ ﾉ ɯ
1 ج° ◊ ﾉ ɯ

↕ ج ج Ω ∩ ن ۱ Ն ج show cpu ج Pts Վ پ

ن ۱ Ն

OAM

cpu

RSR20-14F#show temperature
Device Temperature(C)
------ --------------
CM 42
RSR20-14F#sho environment

Environmental status update at 13:29:13 1993-03-04.
Data is 18 second old, refresh in 20 second(s).
Power Supplies:
Fans working status:
Fan 1 is on.
Fan 2 is on.
Temperature readings:
measured at 42 C
Hardware:
CPU name: OCTEON.
CPU Speed : 500M

RSR20-14E

E1 ♩ ╒ ≡

20-14E/F ◦ ŕ FPGA א cpm ΐ FPGA א ע ע

ℓ loopback DTE ٦ ΐ Φ ع ب ـل

۹ ۸ ۷ ’ ۸ Ạ

- ۲ ۱ ۲ ~
  ۷ ۶ Φ Φ
  ۸ OBJ
- ۱ ن
  ≡ ۸ OBJ پ

˝ ¡ ۱ ک ` ۱RSR20

₱

گ گCPU ת 1 ۶ ف Φ ں ھ ת ز گ ₿ ۽ گ
CPU ת ۳ CPUح ă ھ ں ۶ OBJ چ

₹

ہ ز ۱ ں ھ * أ OBJ ں ھ ă * OBJ چ
⅝ * OBJ ם گCPU ת ن ۸ ۷ ע OBJ
□ أ گ ڈ ת RSR77ں ₱ أ

₹ Ạ

- گCPU ת ۷ CPUح OBJ
- ۱ ₿ گ ک ب۷ ۵ ۷ ۸ ؛ ۶ أ ۷
  ⅝ ۷* ⅛ ۶ أ ARP 10 ۵ ب۷

```
control-plane manage
port-filter
 arp-car 10
 no acpp
```

گ

ۆ ۆ ۆ ۆ

ۆ ۆ ۆ ۆ

```
control-plane
!
control-plane protocol
 no acpp       //
!
control-plane manage
 no port-filter  //
          UDP
 no arp-car    //arp
 no acpp
!
control-plane data
 no glean-car   //
          IP
 no acpp
```

```
control-plane
!
control-plane protocol
no acpp
!
control-plane manage
port-filter
 arp-car 10
 no acpp
!
control-plane data
glean-car 5
 acpp bw-rate 300 bw-burst-rate 600
```

Contents

Φ Ŭ

ﻯ ≠

ﺣ

بﻠ

α̋ 6



ڑ ⊩ ∩ ⊏

- ⋏ ⋀ # ⍵ ⋏ ⋀ ⋏ ⋀ ↾ OBJ h
- ⋏ ⋏ ⊕ ⊾ ⊬ # ⍵ ⋏ ⋏ ⊕ ⊾ ⊬ ■ OBJ ⋏ ⋏ ق
  Φ
- ⋏ ⋏ ⊕ OBJ ج ت ف ↑ # ɹ ⋏ ⋏ OBJ ج ت ↑
  ɲ
- ⋏ ⋏ ⊕ OBJ ت ◦ ◦ # ɹ ⋏ ⋏ OBJ ت ◦ ◦ ɲ h ت ◦ ◦ ∧ ↑
  ت ◦ ◦ ؤ ˋ ⋏
- ip h # ⋏ ⋀ ↾ h OBJ ج ت
  ⊬ip
- OBJ ⅄ ⅂ ↾
- ≠ e ⅋ OBJ ⋏ ⊾ ∂ NAT QOS 3G ⋏

٧ ٦ ت ك ح

- ١٠ ٥ ٢ ٠ u
- ٧ ٦ ت ٨ ٠
- ك ح ٠

- ٥ ٢ ٠ u
- ٧ ٦ ت ٨ ٠
- ك ح ٠

٥ ٢ ٩ ٣ ٦ ٥ ٠

- ٥ ٢ ٩ ٣ ٦ ٥ ٠

٥ ٢ ٩ ٣ ٦ ٥ ٠

- releasenote ك ح PPT ٥ ٢ ٩ ٣ ٦ ٥ ٠





t t

A
B
C
错误的姿势！禁止纵向

-
-
-

-
-

3G

rgos.bin

rgos.bin

tftp

rgos.bin

.doc

RSR

- ٤
- v ٨
- ً

NMX-24ESW ٨ ٨

SIC-3G ٨

SIC-3G ؤ v ث ٠ ٨ ب ğ ء ب ٦ أً
ڈ ئ ٨ ک ح releasenote n * . SIC-3G ؤ v ٨
| ٦ xmodem tftp

- Xmodem ٨ ڑ ڈ ذ ٨ گ □ ٨
- Tftp ٨ ڑ ~ ℓ ح ⅝ ڈ گ ⅈ ث ٠ ٨ جـ SIC-3G ٨

ؤ SIC-3G ٨ | ├ ° ğ RSR٨ ث ٠ SIC-3G ٨ ٨ .doc



```
XWRJ(config )#interface f  0/0
XWRJ(config -if-FastEthernet  0/0)#description   To_BJ
```

```
XWRJ#clock set 12:12:12 1 1 2012
```



flash

```
XWRJ(config)#logging file flash:log.text 2000000
```

loopback 0

```
XWRJ(config )#interface  loopback  0
XWRJ(config -if-Loopback 0)#  ip  add 1.1.1.1 255.255.255.255
```

TELNET

```
XWRJ(config)#enable secret 0 ruijie   //
XWRJ(config)#lin vty 0 4
XWRJ(config -line)#password 0 ruijie
XWRJ(config -line)#login
```

```
Router ( config )# service password  -encryption
```

IP+MAC+ ٧ ٦

- : Ь
- v ٧
- f

h ٣ ٩

٧ + OBJipmacbind

+SVI OBJACL

- ٧ ٦ MAC+ ٧
- Ipmacbind ٦ IP MAC

RSR20-14E/F

3 MSTP

- vlan
- vlan SVI



Contents

Φ Ü

ﻝ

ﻉ ≒

ﻭ

بﻠ

ǟ 6

RSR20 uh¯

- گ ۀ ۽ ۸ h ₩OBJ

۽ ۸ ₽

ɔ ۸

VPN

i

۷ ۸ OBJ 3G ۸




Internet
Internet
Internet



3G BFD TRACK IPSEC /RIP/OSPF

AAA SNMP


RSR50/RSR77
IPSec/GRE
IPSec/GR
E1/ X.25/FR/DDN
PSDN/ISDN

Contents

Φ Ü

ﻝ

ﻉ =

٠ר

ف ﻝ ’

ű α 6


网点
运营商
一级/二级分行
RSR20-14/
主线路
L2TP/GRE隧道
汇聚路由器
/LNS
LAC
3G备份线路
专线/
LAC AAA服务器
LNS AAA服务器
SNC-Pro-3G
IPSec隧道

• ﺓ ﻝ ﺒ ﭖ ﺭ RSR20-14E ﻝ ﺒ ﺙ ﺍ ﭖ ﺭ ﺍ MSTP+ ﺍ 3G
ﺍ ﺙ MSTP ﺍ ﺙ ﭖ ﺭ QOS - 3G ﺍ
ﺙ ﻝ ﺭ ﻅ ﻕ VPDN ﺍ ﭖ ﺭ IPSEC+SM1 ﻝ |

ﺍ ﻝ	ﺍ ﺏ ﻕ	↕
₩	VLAN SVI	ă
3G	3G ﺝ ﺙ ﭖ ﺭ ﺱ ﺙ ﺍ ﺩ 3G ﺱ ﻯ ﻻ keepalive ﭖ ﭖ ﻝ LNS ﺍ IP ﻑ	
IPSEC	ﭖ ﺭ ﺃ ﺓ SM1 ﻝ | ﭖ ﻝ DPD ﻻ	
ﺙ ﺍ ﻥ	ﭖ ﺭ OSPF+ ً ﺙ ﺍ	
DLDP	MSTP ﺝ ﺙ ﻻ	
QOS	MSTP ﺍ ﺙ ﭖ ﺭ LLQ+CBWFQ ﻙ	
ﭖ ﻝ	ﻙ ﻝ ﺍ ﺙ ﻝ telnet ﻟ IP ﺕ	ă
	AAA/SNMP/ACL ﺵ ﺯ /ACL ﮒ ﮈ ⅜ ﻝ ﺯ	ﺭ ﭖ ﻝ

IPSEC

```
ip access-list extended 100                    //  ﺏ ﻟ IPSec      ﺭ      ﷺ
 10 permit ip 10.0.0.0 0.0.0.255 22.144.20.0 0.0.0.255
!
crypto isakmp policy 1
 authentication pre   -share
!
crypto isakmp keepalive 10 2                   //  ﺏ ﻟ DPD   ﷺ
crypto isakmp key 7 06576c507b4044 address 21.147.251.130
crypto ipsec transform   -set myset  esp -sm1   //   ﺓ SM1 ﻝ │   ﺭ
crypto map mymap 1 ipsec   -isakmp
 set peer 21.147.251.130
 set transform  -set myset
 match address 100
!
interface Async 1
 crypto map mymap                              //                ﺓ
!
```



Contents

Φ ΰ

ﻝ

ﻉ ≠

ٶ

ﺑ ﻝ ؕ

ﻝ ”

KOA

3G .doc

2.0 3G

RSR SIC-3G .doc

RSR SIC-3G V1.0.zip

RSR .doc

RSR .doc

RSR20 V1.2.doc

RSR20

RSR .doc

RSR 2.0.rar

谢谢 | 创新网络价值

ﻉ ج ﻉ ﻫ ں
〒╪ ث29 m11 ٧ ﻉ 100036
Office Tel: 010-51718888 Mobile Tel: 13888888888 Fax: 010-51718888
E-Mail: xxx@ruijie.com.cn