





# AC show ap-config summary AP

```

WS18000-1B11#show ap-config summary
-----
Online AP number: 33
Offline AP number: 156

-----
In/off_time  State  AP Name  TR Address  Mac Address  Radio  Radio
-----
02/22/19  08:09:34  temp/2  192.168.1.100  000000000000  wlan1  wlan1
-----
    
```

第三频

# AC show ac-config client

```

WS18000-1B11#show ac-config client
===== show sta status =====
AP : ap name/radio id
State: Stand/Recon/Exec/Work Mode/Reinit/State/MU,MTMO, E= enable, power save, D= disable, power save
-----
TotalSta.Num: 39
STA MAC      IPV4 Address  AP      wlan wlan status  Asso-Auth  Net Auth  Up time
-----
F48b.32a3.04e3  temp/2      6  1731  9.0M/E/ac/R/mu  MAB        WEB        0:20:37:33
WS18000-1B11#
    
```

mu终端

RG-AP820-A(X) console

ap fit

conf

ap-mode fat--- fat

Show run ///

show int status ///

Show version detail ///

show dot wireless 1/0 /// radio

Show dot a a /// sta

RG-AP820-A(X)







RG-AP820-A(X)



RG-AP820-A(X)



Q:

A:

1 RG-AP820-A(X) LAN PoE 802.11af

2

Q:

A:

Q: AP

A:

AP

AP

Q:AP820-A ip

A:

LAN 192.168.110.1

LAN 192.168.110.1

I

Q:

A:

Q:

A:

[www.ruijie.com.cn](http://www.ruijie.com.cn)

[www.ruijie.com.cn/service.aspx](http://www.ruijie.com.cn/service.aspx)

[support.ruijie.com.cn](http://support.ruijie.com.cn)